

WA-736P**Multifunctional CCTV Tester****Key Features**

- ▶ Display: 2.5 inch LTPS LCD screen; 960 x 240 resolutions
- ▶ Signal Mode: NTSC/PAL automatically suitable
- ▶ Test the Video signal and the quality of picture
- ▶ Test of PTZ Products, function includes pan/tilt, zoom in/out
- ▶ Preset setting and operation, auto scanning, speed adjustment etc
- ▶ Support multi-protocol and baud rate
- ▶ Test the wiring condition of UTP Cable, the data can be shown on the screen
- ▶ Generate the video signal; the generation signal supports PAL/NTSC System
- ▶ Test the RS485 Data; display the hexadecimal data content for engineer to analyze
- ▶ With an interface to supply power to the camera

Technical Specification

Model	WA-736P
Signal Mode	NTSC/PAL automatically suitable
Display	2.5 inch LTPS LCD screen , 960 x 240 resolution
Video Input/Output	1 Channel BNC
Communication	RS485, RS422 Simplex
Protocol	Pelco- D/P; Samsung, ADT, YAAN, HY, LG, Minking, VIDO, Videotrec or customized.
Baud Rate	1200, 2400, 4800, 9600, 19200bps
Supply power to camera	Supply power interface on the left of CCTV tester, DC12V/700m
UTP Cable Test	Test UTP Cable connection state and display on the screen.
RS485 Data Test	Test the RS485 data sent from control device.
OSD Menu	English
Keyboard	New design with number buttons, easy to operation.
Power Supply	DC9V/2000MA
Battery	1 pc Li-polymer rechargeable battery 7.4V, capacity 2000mAh
Rechargeable	5 hours recharging time, work for 8 hours or more.
Low Consumption	Sleeping mode, display battery power status.
Work Temperature	-30°C~+70°C
Work Humidity	30%~90%
Dimension	165*104*43 mm